




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : G01L 1/24, G01D 5/353		A1	(11) International Publication Number: WO 00/57148
		(43) International Publication Date: 28 September 2000 (28.09.00)	
(21) International Application Number: PCT/GB00/00994 (22) International Filing Date: 17 March 2000 (17.03.00) (30) Priority Data: 9906361.2 19 March 1999 (19.03.99) GB (71) Applicant (for all designated States except US): MARCONI CASWELL LIMITED [GB/GB]; One Bruton Street, London W1X 8AQ (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): GROVES-KIRKBY, Christopher [GB/GB]; 19 West End, Bugbrooke, Northampton NN7 3PF (GB). BENNION, Ian [GB/GB]; 25 Guilsborough Road, Ravensthorpe, Northampton NN6 8EW (GB). WILLIAMS, John [GB/GB]; 15 Deanbrook Close, Shirley, Solihull, West Midlands B90 4XS (GB). ZHANG, Lin [CN/GB]; 71 Solihull Lane, Hall Green, Birmingham B28 9LT (GB). (74) Agent: HOSTE, Colin, Francis; Marconi Intellectual Property, Waterhouse Lane, Chelmsford, Essex CM1 2QX (GB).		(81) Designated States: AU, CA, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.	

(54) Title: STRAIN SENSING



(57) Abstract

A strain sensor comprises an optical waveguide (6) having a plurality of reflecting structures (Bragg gratings) along its length. Each structure reflects light at a different characteristic wavelength (λ_1 to λ_{n+1}) which changes in dependence on a change of physical length of at least part of the reflecting structure. The reflectivity of reflecting structures which reflect at characteristic wavelengths which are adjacent to each other (λ_1 and λ_2 or λ_n and λ_{n+1}) are configured to be different such that the intensity of light reflected from adjacent structures can be used to discriminate between them.